





TECH SPECS

COMPATIBILITY

Conventional (2H/2C)—Gas, oil, electric. Boiler (2-stage-heating).

Air-Cooled & Geo-Thermal Heat pumps (2 stage heat pump + 2 stage aux heat/2 cool) (4H/2C).

Dual-Fuel support.

WIRE TERMINALS

RC	O/B	W1
G	RH	W2
Y1	С	PEK
Y2		

POWERING METHOD

Wired 24VAC through terminals C or Rc. Power Extender Kit enables you to reliably power your thermostat without having to run a C wire.

POWER CONSUMPTION

Less than 3.5VA

CONNECTIVITY AND SECURITY

Wi-Fi, IEEE 802.11 b/g/n @ 2.4 GHz Wi-Fi Protected Access (WPA/WPA2) Wired Equivalent Privacy (WEP) DHCP (dynamic) or static IP addressing Transport Layer Security (TLS) 915MHz

BANDWIDTH

15-20 MB/month

SUSTAINABILITY

Mercury free Arsenic free PVC free

ROHS compliant

THERMOSTAT SENSORS

Temperature Proximity Humidity

ROOM SENSOR

Temperature Motion

TEMPERATURE RANGE

Temperature: 7° to 33°C (45° to 92°F)
Display: 5° to 37°C (40° to 100°F)
Sensitivity: +/- 0.5°C (+/- 1°F)
Operating: 0° to 55°C (32° to 130°F)

HUMIDITY RANGE

Display: 20% to 90% RH Sensitivity: +/- 5% RH

Operating: 5% to 95% RH (non condensing)

STORAGE

-35° to 45°C (-31° to 113°F) 5% to 95% RH (non condensing)

LANGUAGES

English

DISPLAY

3.5" full-color LCD touch screen320 x 480 pixel display

HOMEKIT-ENABLED

HomeKit requires an iPhone, iPad, or iPod touch with iOS 9 or later. Controlling HomeKit-enabled accessories away from home requires an Apple TV with tvOS 9.0 or later and an iPhone, iPad, or iPod touch with iOS 9 or later.

WARRANTY

5-year warranty (PRO Install only)

WHAT'S IN THE BOX

ecobee3 lite thermostat

Install guide
Backplate
Trim plate
Screws
Dry wall plugs
Wire labels

Power Extender Kit

PRODUCT DIMENSIONS

Thermostat

Length: 102.88 mm Width: 102.88 mm Depth: 21.4 mm

Trim Plate

Length: 170 mm Width: 170 mm Depth: 6.25 mm

Length: 62.1 mm Width: 60.1 mm Depth: 21.4 mm

Power Extender Kit









